

View Online at <https://aerobasegroup.com/nsn/5935-01-317-5061>

Body Style:

Straight shape w/strain relief

Overall Length:

5.033 inches

Overall Diameter:

2.219 inches

Environmental Protection:

Dripproof and weather resistant and watertight and dustproof and corrosion resistant and chemical resistant and pressure proof and shock resistant and vibration resistant and humidity resistant and moisture resistant

Mating End Quantity:

1

Contact Position Arrangement Style:

3 single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

30.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

480.0 single mating end single contact grouping

Polarization Method:

Key, multiple key groove

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Connector Cable Strain Relief Method:

Shrinkable tubing

End Application:

4920-01-210-6697 adapter kit, depot test cell

Operating Temperature Rating:

Between -80.0 degrees fahrenheit and 275.0 degrees fahrenheit

Features Provided:

Arc quenching

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper single mating end single contact grouping

Contact Surface Treatment:

Silver single mating end single contact grouping and copper single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Aluminum

Shell Surface Treatment:

Anodize

Included Contact Quantity:

3 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces silver

Precious Material And Weight:

0.003 silver grains, troy

Precious Material:

Silver

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0