NSN 5935-01-317-6538

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-317-6538 **Thread Class:** 2a and 2a **Thread Direction:** Right-hand and right-hand **Body Style:** Straight shape threaded **Overall Length:** 1.531 inches **Overall Diameter:** Between 2.240 inches and 2.260 inches **Distance From Mounting Shoulder To Front Face:** Between 1.209 inches and 1.229 inches **Mounting Facility Thickness:** 0.298 inches **Threaded Device Type:** Coupling facility and mounting bushing **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 28-21 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 13.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 700.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 **Shell Type:** Solid **Connector Locking Method:** Externally threaded shell

Thready Qty Per Inch (tpi):

18 and 18

Thread Size:

1.750 inches and 1.750 inches

Terminal Location:

Back single mating end single contact grouping

NSN 5935-01-317-6538

Electrical Receptacle Connector - Page 2 of 2



Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Silver single mating end single contact grouping
Insert Material:
Plastic single mating end
Contact Surface Treatment Specification:
Qq-s-365 federal specification single treatment response single mating end single contact grouping
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum
Shell Surface Treatment:
Cadmium and chromate
Included Contact Quantity:
37 single mating end single contact grouping
Bushing Accommodation Hole Shape:
Round
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces silver
Precious Material And Weight:
0.037 silver grains, troy
Precious Material:
Silver
Thread Series Designator:
Uns and uns
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0