## NSN 5935-01-317-7687

**Thread Class:** 

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-317-7687

20
Thread Direction:
Right-hand
Body Style:
Angle shape w/cable clamp
Overall Diameter:
2.469 inches
Body Angle In Deg:
90.0
Environmental Protection:
Moisture resistant and vibration resistant
Cable Entrance Diameter:
1.250 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
36a34 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Internally threaded coupling ring
Connector Cable Strain Relief Method:
Cable clamp
Distance From Centerline To Connector End:
2.836 inches
Distance From Centerline To Cable End:
2.719 inches
Operating Tempurature Rating:

Between -55.0 degrees celsius and 125.0 degrees celsius

## **NSN 5935-01-317-7687**Electrical Plug Connector - Page 2 of 2



Thread Size: 2.250 inches  Terminal Location: Back single mating end single contact grouping  Contact Material: Copper alloy single mating end single contact grouping  Contact Surface Treatment: Silver single mating end single contact grouping  Insert Material: Rubber synthetic single mating end
2.250 inches  Terminal Location:  Back single mating end single contact grouping  Contact Material:  Copper alloy single mating end single contact grouping  Contact Surface Treatment:  Silver single mating end single contact grouping  Insert Material:
Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping Insert Material:
Back single mating end single contact grouping  Contact Material:  Copper alloy single mating end single contact grouping  Contact Surface Treatment:  Silver single mating end single contact grouping  Insert Material:
Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping Insert Material:
Copper alloy single mating end single contact grouping  Contact Surface Treatment:  Silver single mating end single contact grouping  Insert Material:
Contact Surface Treatment: Silver single mating end single contact grouping Insert Material:
Silver single mating end single contact grouping  Insert Material:
Insert Material:
Rubber synthetic single mating end
reader symmetre emigre maning ema
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and chromate
Shell Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification all treatment responses
Included Contact Quantity:
52 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces silver
Precious Material And Weight:
0.052 silver grains, troy
Precious Material:
Silver
Thread Series Designator:
Un
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0