

View Online at <https://aerobasegroup.com/nsn/5935-01-317-7710>

**Body Style:**

Straight shape

**Overall Length:**

2.706 inches

**Overall Height:**

0.370 inches

**Overall Width:**

0.240 inches

**Environmental Protection:**

Thermal shock resistant and humidity resistant and vibration resistant and shock resistant and salt water resistant

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

2 rows of contacts non-inserted board single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

1.0 single mating end single contact grouping

**Connector Locking Method:**

Friction

**Operating Temperature Rating:**

Between -55.0 degrees celsius and 105.0 degrees celsius

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

**Insert Material:**

Plastic polyamide single mating end and glass single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204 military specification 1st treatment response single mating end single contact grouping and qq-n-290 federal specification 2nd treatment response single mating end single contact grouping

**Terminal Type:**

Printed circuit single mating end single contact grouping

**Contact Material Specification:**

Qq-b-750, full hard federal specification single material response single mating end single contact grouping

**Included Contact Quantity:**

54 single mating end single contact grouping

**Included Contact Type:**

Square socket single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.054 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.