NSN 5935-01-317-9339

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-317-9339

Body Style:

Straight shape, external coupling

Overall Length:

Between 1.319 inches and 1.341 inches

Overall Height:

Between 2.233 inches and 2.255 inches

Overall Width:

Between 2.233 inches and 2.255 inches

Environmental Protection:

Corrosion resistant and fungus resistant

Unthreaded Mounting Hole Diameter:

0.169 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 1.748 inches and 1.754 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 1.748 inches and 1.754 inches

Distance From Mounting Shoulder To Front Face:

Between 0.931 inches and 0.961 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

32-6 single mating end

Contact Removability:

Removable single mating end all contact groupings

Contact Maximum Current Rating In Amps:

74.0 single mating end 3rd contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Bayonet slot

Operating Tempurature Rating:

Between -55.0 degrees celsius and 125.0 degrees celsius

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

Contact Surface Treatment:

Silver single mating end 3rd contact grouping

NSN 5935-01-317-9339

Electrical Receptacle Connector - Page 2 of 2



Insert Material:
Rubber chloroprene class cr single mating end
Contact Surface Treatment Specification:
Qq-s-365 federal specification single treatment response single mating end 3rd contact grouping
Terminal Type:
Crimp single mating end all contact groupings
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and chromate
Included Contact Quantity:
3 single mating end 3rd contact grouping
Included Contact Type:
Round pin single mating end all contact groupings
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.026 gold grains, troy and 0.025 silver grains, troy
Precious Material:
Gold and silver
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.