NSN 5935-01-318-2907



Electrical Receptacle Connector Body - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-01-318-2907 **Thread Class:** 2a and 2b and 2a **Thread Direction:** Right-hand and right-hand and right-hand **Body Style:** Rectangular shape **Overall Length:** 2.906 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 2.375 inches **Overall Height:** 0.890 inches **Overall Width:** 1.531 inches **Environmental Protection:** Humidity resistant and shock resistant and thermal shock resistant and vibration resistant Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.875 inches **Threaded Device Type:** Coupling facility and mounting stud **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 25-104 single mating end **Polarization Method:** Shell and jackscrew Shell Type:

Solid

Connector Locking Method:

Jackscrew-socket

Thready Qty Per Inch (tpi):

32 and 32 and 32

Thread Size:

0.164 inches and 0.164 inches and 0.138 inches

Insert Material:

Plastic diallyl phthalate single mating end

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Anodize

Insert Material Specification:

Mil-m-14, ty sdg-f military specification single material response single mating end

NSN 5935-01-318-2907

Electrical Receptacle Connector Body - Page 2 of 2



Shell Guide Type And Location Designator:
B slot
Unable To Decode:
Unable to decode and unable to decode
Thread Series Designator:
Unc and unc and unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):

Mil-m-14 spec.