## NSN 5935-01-318-3051

**Thread Class:** 

2a

Electrical Receptacle Connector - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5935-01-318-3051



**Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.405 inches **Overall Diameter:** 1.250 inches **Environmental Protection:** Moisture proof and shock proof and vibration proof **Distance From Mounting Shoulder To Front Face:** Between 0.431 inches and 0.462 inches **Mounting Facility Thickness:** 0.062 inches **Threaded Device Type:** Back shell **Mating End Quantity: Contact Position Arrangement Style:** 14-12 single mating end **Contact Removability:** Removable single mating end all contact groupings **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 43.0 Shell Type: Solid Thready Qty Per Inch (tpi): **Thread Size:** 0.875 inches **Terminal Location:** Back single mating end all contact groupings **Contact Material:** Copper alloy single mating end all contact groupings **Contact Surface Treatment:** Gold single mating end all contact groupings and nickel single mating end all contact groupings **Terminal Type:** Crimp single mating end all contact groupings

## NSN 5935-01-318-3051

Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Aluminum
Shell Surface Treatment:
Cadmium
Included Contact Quantity:
8 single mating end 2nd contact grouping
Included Contact Type:
Round pin single mating end all contact groupings
Precious Material:
Gold
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0