## NSN 5935-01-318-4039

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-318-4039

**Body Style:** 

Straight shape, rectangular

**Overall Length:** 

1.173 inches

**Overall Height:** 

Between 1.850 inches and 1.870 inches

**Overall Width:** 

Between 2.865 inches and 2.885 inches

**Environmental Protection:** 

Humidity resistant and shock resistant and thermal shock resistant and vibration resistant

**Unthreaded Mounting Hole Diameter:** 

Between 0.143 inches and 0.155 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 1.245 inches and 1.255 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 2.495 inches and 2.505 inches

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

158 single mating end

**Contact Removability:** 

Removable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:** 

7.5 single mating end single contact grouping

**Connector Locking Method:** 

Friction

**Operating Tempurature Rating:** 

Between -55.0 degrees celsius and 125.0 degrees celsius

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping and nickel single mating end single contact grouping

**Insert Material:** 

Plastic diallyl phthalate glass filled single mating end

**Contact Surface Treatment Specification:** 

Mil-g-45204, type 2, grade c, cl 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 2 federal specification 2nd treatment response single mating end single contact grouping

**Terminal Type:** 

Crimp single mating end single contact grouping

**Contact Material Specification:** 

Qq-c-530 federal specification single material response single mating end single contact grouping or qq-c-533 federal specification single material response single mating end single contact grouping

# NSN 5935-01-318-4039

Electrical Receptacle Connector - Page 2 of 2



#### **Insert Material Specification:**

Mil-m-14, ty sdg-f military specification single material response single mating end or mil-p-19833, ty gdi-30f military specification single material response single mating end

## **Included Contact Quantity:**

158 single mating end single contact grouping

#### **Included Contact Type:**

Round socket single mating end single contact grouping

#### **Precious Material And Location:**

Contact surfaces gold

## **Precious Material And Weight:**

0.158 gold grains, troy

#### **Precious Material:**

Gold

### **Test Data Document:**

81349-mil-c-28748 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Specification Data:**

81349-mil-c-28748/10 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No

Fiig:

A039b0

## Mil-std (military Standard):

Mil-g-45204 spec.