Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-318-4039

## Body Style:

Straight shape, rectangular

## **Overall Length:**

1.173 inches

### **Overall Height:**

Between 1.850 inches and 1.870 inches

### **Overall Width:**

Between 2.865 inches and 2.885 inches

### **Environmental Protection:**

Humidity resistant and shock resistant and thermal shock resistant and vibration resistant

### **Unthreaded Mounting Hole Diameter:**

Between 0.143 inches and 0.155 inches

## Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 1.245 inches and 1.255 inches

## Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 2.495 inches and 2.505 inches

### Mating End Quantity:

1

### **Contact Position Arrangement Style:**

158 single mating end

## **Contact Removability:**

Removable single mating end single contact grouping

## **Contact Maximum Current Rating In Amps:**

7.5 single mating end single contact grouping

## **Connector Locking Method:**

Friction

## **Operating Tempurature Rating:**

Between -55.0 degrees celsius and 125.0 degrees celsius

## **Terminal Location:**

Back single mating end single contact grouping

### **Contact Material:**

Copper alloy single mating end single contact grouping

## **Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

# Insert Material:

Plastic diallyl phthalate glass filled single mating end

# Contact Surface Treatment Specification:

Mil-g-45204, type 2, grade c, cl 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 2 federal specification 2nd treatment response single mating end single contact grouping

# Terminal Type:

Crimp single mating end single contact grouping

# **Contact Material Specification:**

Qq-c-530 federal specification single material response single mating end single contact grouping or qq-c-533 federal specification single material response single mating end single contact grouping



## **Insert Material Specification:**

Mil-m-14, ty sdg-f military specification single material response single mating end or mil-p-19833, ty gdi-30f military specification single material response single mating end

### **Included Contact Quantity:**

158 single mating end single contact grouping

### Included Contact Type:

Round socket single mating end single contact grouping

**Precious Material And Location:** 

Contact surfaces gold

#### **Precious Material And Weight:**

0.158 gold grains, troy

#### **Precious Material:**

Gold

### Test Data Document:

81349-mil-c-28748 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Specification Data:**

81349-mil-c-28748/10 government specification

Shelf Life:

N/a

## Unit Of Measure:

Demilitarization:

No

--

Fiig:

#### A039b0

Mil-std (military Standard):

Mil-g-45204 spec.