NSN 5935-01-318-6653

Body Style:

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-318-6653

Right angle type **Overall Length:** 3.195 inches **Overall Height:** 0.760 inches **Body Length:** 0.560 inches **Body Width:** 0.390 inches **Environmental Protection:** Shock resistant and vibration resistant and corrosion resistant and humidity resistant and fungus resistant **Unthreaded Mounting Hole Diameter:** Between 0.124 inches and 0.130 inches **Distance Between Mounting Facility Centers:** Between 2.865 inches and 2.885 inches **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 2 rows of contacts non-inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Polarization Method:** Mating end **Connector Locking Method:** Friction **Operating Tempurature Rating:** Between -65.0 degrees celsius and 125.0 degrees celsius **Terminal Location:** Side single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and nickel single mating end single contact grouping **Insert Material:** Plastic single mating end and glass single mating end **Contact Surface Treatment Specification:**

Terminal Type:

Printed circuit single mating end single contact grouping

federal specification 2nd treatment response single mating end single contact grouping

Contact Material Specification:

Qq-b-626 federal specification single material response single mating end single contact grouping or qq-b-750 federal specification single material response single mating end single contact grouping or qq-c-530 federal specification single material response single mating end

Mil-g-45204, type 2, grade c, cl 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290

NSN 5935-01-318-6653

Electrical Receptacle Connector - Page 2 of 2



Insert Material	Specification:
-----------------	----------------

Mil-m-24519, ty gpt-15f military specification all material responses single mating end

Included Contact Quantity:

38 single mating end single contact grouping

Included Contact Type:

Brush pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.038 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-55302 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-c-55302/168 government specification

Shelf Life:

N/a

Unit Of Measure:

-

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.