NSN 5935-01-318-8069

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-318-8069

Body Style:

Straight edge type w/mounting flange

Overall Length:

Between 1.860 inches and 1.890 inches

Overall Height:

0.632 inches

Overall Width:

Between 0.320 inches and 0.340 inches

Unthreaded Mounting Hole Diameter:

Between 0.115 inches and 0.135 inches

Distance Between Mounting Facility Centers:

Between 1.570 inches and 1.580 inches

Board Accommodated Length:

1.100 inches single board and 1.114 inches single board

Board Accommodated Width:

Between 0.054 inches and 0.071 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of independent contacts inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

600.0 single mating end single contact grouping

Polarization Method:

Inter-contact polarizing keys

Connector Locking Method:

Friction

Operating Tempurature Rating:

Between -65.0 degrees celsius and 105.0 degrees celsius

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, grade c military specification 1st treatment response single mating end single contact grouping

NSN 5935-01-318-8069

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:
Printed circuit single mating end single contact grouping
Insert Material Specification:
Mil-m-14 military specification single material response single mating end
Included Contact Quantity:
20 single mating end single contact grouping
Included Contact Type:
Bifurcated spring single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.020 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.

Demilitarization: