

View Online at <https://aerobasegroup.com/nsn/5935-01-319-1665>

Body Style:

Straight shape, external/internal coupling

Overall Length:

Between 2.947 inches and 2.967 inches

Overall Diameter:

Between 0.750 inches and 0.770 inches

Environmental Protection:

Moisture resistant and shock resistant and thermal shock resistant and vibration resistant

Mating End Quantity:

2

Contact Position Arrangement Style:

Nonstd all mating ends

Contact Removability:

Nonremovable all mating ends all contact groupings

Shell Type:

Solid

Connector Locking Method:

Bayonet pin and bayonet slot

Contact Material:

Copper alloy all mating ends all contact groupings

Contact Surface Treatment:

Gold all mating ends all contact groupings

Insert Material:

Plastic polytetrafluoroethylene all mating ends or plastic polyamide all mating ends

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response all mating ends all contact groupings

Shell Material:

Copper alloy

Included Contact Quantity:

1 2nd mating end single contact grouping

Included Contact Type:

Triaxial socket 2nd mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.010 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.