

View Online at <https://aerobasegroup.com/nsn/5935-01-319-3019>

**Body Style:**

Right angle type

**Overall Length:**

Between 2.714 inches and 2.744 inches

**Overall Width:**

0.671 inches

**Body Height:**

Between 0.479 inches and 0.509 inches

**Unthreaded Mounting Hole Diameter:**

Between 0.115 inches and 0.125 inches

**Distance Between Mounting Facility Centers:**

Between 2.495 inches and 2.505 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

21 single mating end

**Contact Removability:**

Nonremovable single mating end 1st contact grouping

**Contact Maximum Current Rating In Amps:**

5.0 single mating end 1st contact grouping

**Polarization Method:**

Mating end

**Shell Type:**

Solid

**Connector Locking Method:**

Friction

**Operating Temperature Rating:**

Between -65.0 degrees celsius and 150.0 degrees celsius

**Terminal Location:**

Side single mating end 1st contact grouping

**Contact Material:**

Copper alloy single mating end 1st contact grouping

**Contact Surface Treatment:**

Gold single mating end 1st contact grouping and nickel single mating end 1st contact grouping

**Insert Material:**

Plastic diallyl phthalate glass filled single mating end

**Terminal Type:**

Printed circuit single mating end 1st contact grouping

**Shell Material:**

Steel

**Shell Surface Treatment:**

Chromate and cadmium

**Shell Surface Treatment Specification:**

Qq-p-416, type 2, cl 1 federal specification all treatment responses

**Shell Material Specification:**

Astm-a-620 assn standard single material response

**Insert Material Specification:**

Mil-m-14, ty sdg-f military specification single material response single mating end

**Included Contact Quantity:**

17 single mating end 1st contact grouping

**Included Contact Type:**

Round pin single mating end 1st contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.017 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-m-14 spec.