

View Online at <https://aerobasegroup.com/nsn/5935-01-319-4764>

Thread Class:

2b

Thread Direction:

Right-hand

Body Style:

Straight shape, rectangular

Overall Length:

Between 1.140 inches and 1.200 inches

Overall Height:

Between 1.080 inches and 1.100 inches

Overall Width:

Between 2.265 inches and 2.285 inches

Environmental Protection:

Heat resistant

Unthreaded Mounting Hole Diameter:

0.149 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 0.540 inches and 0.560 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 1.890 inches and 1.910 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

52 single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

13.0 single mating end single contact grouping

Polarization Method:

Polarization boss

Connector Locking Method:

Post jacksocket

Operating Temperature Rating:

Between -54.0 degrees celsius and 125.0 degrees celsius

Thread Qty Per Inch (tpi):

28

Thread Size:

0.250 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, grade c or d class military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Contact Material Specification:

Qq-b-626 federal specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-m-14, ty sdg-f military specification single material response single mating end

Included Contact Quantity:

52 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.052 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.