Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-319-4764

Thread Class:
2b
Thread Direction:
Right-hand
Body Style:
Straight shape, rectangular
Overall Length:
Between 1.140 inches and 1.200 inches
Overall Height:
Between 1.080 inches and 1.100 inches
Overall Width:
Between 2.265 inches and 2.285 inches
Environmental Protection:
Heat resistant
Unthreaded Mounting Hole Diameter:
0.149 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
Between 0.540 inches and 0.560 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Between 1.890 inches and 1.910 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
52 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
13.0 single mating end single contact grouping
Polarization Method:
Polarization boss
Connector Locking Method:
Post jacksocket
Operating Tempurature Rating:
Between -54.0 degrees celsius and 125.0 degrees celsius
Thready Qty Per Inch (tpi):
28
Thread Size:
0.250 inches
Terminal Location:
Back single mating end single contact grouping



Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 2, grade c or d class military specification single treatment response single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Contact Material Specification:
Qq-b-626 federal specification single material response single mating end single contact grouping
Insert Material Specification:
Mil-m-14, ty sdg-f military specification single material response single mating end
Included Contact Quantity:
52 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.052 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Filg:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.