NSN 5935-01-319-9933

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-319-9933 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Straight shape, flush mount **Overall Length:** Between 1.046 inches and 1.076 inches **Overall Height:** Between 3.060 inches and 3.090 inches **Overall Width:** Between 1.985 inches and 2.015 inches **Environmental Protection:** Cold resistant and heat resistant Center To Center Distance Between Mounting Facilities Parallel To Height: Between 2.778 inches and 2.788 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 1.432 inches and 1.442 inches **Distance From Mounting Shoulder To Front Face:** Between 0.045 inches and 0.075 inches **Threaded Device Type:** Mounting hole **Mating End Quantity: Contact Position Arrangement Style:** "106, a106" all mating ends **Contact Removability:** Removable all mating ends single contact grouping **Polarization Method:** Guide pin/socket Shell Type: **Connector Locking Method:** Friction **Operating Tempurature Rating:** Between -65.0 degrees celsius and 125.0 degrees celsius Thready Qty Per Inch (tpi): 40 **Thread Size:** 0.112 inches

Terminal Location:

Back all mating ends single contact grouping

NSN 5935-01-319-9933

Electrical Receptacle Connector - Page 2 of 2



Contact Material:
Copper alloy all mating ends single contact grouping
Contact Surface Treatment:
Gold all mating ends single contact grouping
Insert Material:
Plastic all mating ends
Contact Surface Treatment Specification:
Mil-g-45204, type 1, grade c, class 1 military specification single treatment response all mating ends single contact grouping
Terminal Type:
Crimp all mating ends single contact grouping
Guide Design And Location:
Hexagon shape male post left-hand at 10 oclock and hexagon shape male post center at 10 oclock and hexagon shape male post
right-hand at 10 oclock
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and chromate
Shell Surface Treatment Specification:
Qq-p-416, type 2, class 3 federal specification all treatment responses
Included Contact Quantity:
106 all mating ends single contact grouping
Included Contact Type:
Round socket all mating ends single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.212 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

Mil-g-45204 spec.

Mil-std (military Standard):

A039b0