NSN 5935-01-319-9938

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-319-9938

Body Style:

Angle shape, pcb type

Overall Length:

2.540 inches

Overall Height:

0.370 inches

Overall Width:

Between 0.575 inches and 0.585 inches

Environmental Protection:

Humidity resistant and salt water resistant and thermal shock resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

Between 0.057 inches and 0.067 inches

Distance Between Mounting Facility Centers:

Between 2.335 inches and 2.345 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Friction

Operating Tempurature Rating:

Between -55.0 degrees celsius and 105.0 degrees celsius

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy 260 single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic polyamide single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2 military specification 1st treatment response single mating end single contact grouping

Terminal Type:

Printed circuit single mating end single contact grouping

Contact Material Specification:

Qq-b-613 federal specification single material response single mating end single contact grouping

NSN 5935-01-319-9938

Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Aluminum alloy 6061
Shell Surface Treatment:
Anodize
Shell Surface Treatment Specification:
Mil-a-8625, type 2 military specification single treatment response
Shell Material Specification:
Qq-a-200/8 federal specification single material response
Insert Material Specification:
Mil-m-20693, type 1 military specification single material response single mating end
Included Contact Quantity:
40 single mating end single contact grouping
Included Contact Type:
Flat pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.040 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.