

View Online at <https://aerobasegroup.com/nsn/5935-01-319-9947>

Body Style:

Straight shape

Overall Length:

2.850 inches

Overall Height:

1.070 inches

Overall Width:

0.340 inches

Body Length:

2.060 inches

Distance Between Mounting Facility Centers:

1.900 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

1.0 single mating end single contact grouping

Polarization Method:

Mating end

Connector Locking Method:

Latch

Operating Temperature Rating:

Between -55.0 degrees celsius and 105.0 degrees celsius

Features Provided:

Pre-tinned terminal

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic polyester glass filled single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, grade c military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 2 federal specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Printed circuit single mating end single contact grouping

Included Contact Quantity:

26 single mating end single contact grouping

Included Contact Type:

Square pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.026 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.