NSN 5935-01-319-9949

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-319-9949

Body Style:

Straight shape

Overall Length:

Between 2.073 inches and 2.103 inches

Overall Height:

0.653 inches

Overall Width:

Between 0.479 inches and 0.509 inches

Environmental Protection:

Corrosion resistant and humidity resistant and shock resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

Between 0.115 inches and 0.125 inches

Distance Between Mounting Facility Centers:

Between 1.847 inches and 1.857 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

25 single mating end

Contact Removability:

Removable single mating end single contact grouping

Polarization Method:

Mating end

Shell Type:

Solid

Connector Locking Method:

Friction

Operating Tempurature Rating:

Between -55.0 degrees celsius and 125.0 degrees celsius

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate glass filled single mating end or plastic polyester glass filled single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, grade c, cl 1 military specification 1st treatment response single mating end single contact grouping or qq-n-290, cl 2 federal specification 2nd treatment response single mating end single contact grouping

Crimping Tool Identifying Number:

96906-ms18278-1

Terminal Type:

Crimp single mating end single contact grouping

NSN 5935-01-319-9949

Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Metal
Shell Surface Treatment:
Cadmium
Insert Material Specification:
Mil-m-14, ty sdg-f military specification 1st material response single mating end or mil-m-24519, ty gpt-30f or ty get-30f military specification
2nd material response single mating end
Included Contact Quantity:
25 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.025 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-24308 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-c-24308/6 government specification
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.