## NSN 5935-01-320-2509

Connector Adapter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-320-2509 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Straight shape, internal coupling **Overall Length:** 2.130 inches **Overall Diameter:** 0.880 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** Hn all mating ends **Contact Removability:** Nonremovable all mating ends single contact grouping **Contact Maximum Frequency Rating:** 4.0 gigahertz all mating ends single contact grouping Shell Type: Solid **Connector Locking Method:** Internally threaded shell Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 all mating ends single contact grouping Thready Qty Per Inch (tpi): 20 Thread Size: 0.750 inches **Contact Material:** Copper alloy all mating ends single contact grouping **Contact Surface Treatment:** Gold all mating ends single contact grouping **Insert Material:** Plastic all mating ends **Contact Surface Treatment Specification:** Mil-g-45204 military specification single treatment response all mating ends single contact grouping **Shell Material:** Stainless steel

**Passivate** 

**Shell Surface Treatment:** 

## NSN 5935-01-320-2509

Connector Adapter - Page 2 of 2



Included Contact Quantity:
1 all mating ends single conta

ntact grouping

**Included Contact Type:** 

Coaxial pin all mating ends single contact grouping

**Precious Material And Location:** 

Contact surfaces gold

**Precious Material And Weight:** 

0.010 gold grains, troy

**Precious Material:** 

Gold

**Thread Series Designator:** 

Unef

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.