

View Online at <https://aerobasegroup.com/nsn/5935-01-320-2520>

Body Style:

Straight shape

Overall Length:

Between 8.815 inches and 8.825 inches

Overall Height:

Between 0.690 inches and 0.700 inches

Overall Width:

Between 0.490 inches and 0.510 inches

Unthreaded Mounting Hole Diameter:

Between 0.130 inches and 0.136 inches

Distance Between Mounting Facility Centers:

Between 8.490 inches and 8.510 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

4 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

300.0 single mating end single contact grouping

Polarization Method:

Guide pin/socket

Shell Type:

Solid

Connector Locking Method:

Friction

Operating Temperature Rating:

Between -55.0 degrees celsius and 105.0 degrees celsius

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate glass filled single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, cl 1, grade c military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 1 federal specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Pin single mating end single contact grouping

Guide Design And Location:

D shape pin right-hand top at 2 oclock

Shell Material:

Aluminum alloy 6061 or aluminum alloy 6063

Shell Surface Treatment:

Anodize

Shell Surface Treatment Specification:

Mil-a-8625, type 2, cl 2 military specification single treatment response

Shell Material Specification:

Qq-a-200/8, t6 federal specification 1st material response or qq-a-200/9 federal specification 2nd material response

Insert Material Specification:

Mil-m-14, ty sdg-f military specification single material response single mating end

Included Contact Quantity:

304 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.304 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.