

View Online at <https://aerobasegroup.com/nsn/5935-01-320-4032>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Right angle type

Overall Length:

4.600 inches

Overall Height:

0.625 inches

Overall Width:

0.340 inches

Unthreaded Mounting Hole Diameter:

0.096 inches

Distance Between Mounting Facility Centers:

4.300 inches

Threaded Device Type:

Mounting stud

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

1000.0 single mating end single contact grouping

Polarization Method:

Guide pin/socket

Connector Locking Method:

Friction

Thready Qty Per Inch (tpi):

56

Thread Size:

0.086 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Nickel single mating end single contact grouping and gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Terminal Type:

Solder well single mating end single contact grouping

Contact Material Specification:

Qq-b-750, composition a federal specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-m-14f, type sdgf military specification single material response single mating end

Unable To Decode:

Unable to decode and unable to decode

Included Contact Quantity:

72 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.072 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14f spec.