Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-320-4948

Body Style:

Straight edge type w/mounting flange

Overall Length:

2.723 inches

Overall Height:

0.690 inches

Overall Width:

0.340 inches

Unthreaded Mounting Hole Diameter:

0.128 inches

Distance Between Mounting Facility Centers:

2.469 inches

Board Accommodated Length:

2.036 inches single board

Board Accommodated Width:

0.062 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of independent contacts inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Connector Locking Method:

Friction

End Application:

5811-01-088-0549 demultiplexer

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate glass filled single mating end

Terminal Type:

Tab, solder lug single mating end single contact grouping

Insert Material Specification:

Mil-m-14, ty sdg-f military specification single material response single mating end

Included Contact Quantity:

24 single mating end single contact grouping

Included Contact Type:

Bifurcated spring single mating end single contact grouping



Precious Material And Location: Contact surfaces gold Precious Material And Weight: 0.024 gold grains, troy Precious Material: Gold Shelf Life: N/a Unit Of Measure: --Demilitarization: No Fiig: A039b0

Mil-std (military Standard):

Mil-m-14 spec.