NSN 5935-01-320-6912

Body Style:

Overall Length: 3.697 inches

Angle shape, pcb type

Electrical Receptacle Connector - Page 1 of 2

Printed circuit single mating end single contact grouping

Contact Material Specification:



View Online at https://aerobasegroup.com/nsn/5935-01-320-6912

Overall Height:
0.945 inches
Overall Width:
0.878 inches
Environmental Protection:
Shock resistant and vibration resistant and corrosion resistant and humidity resistant and fungus resistant
Unthreaded Mounting Hole Diameter:
0.100 inches
Distance Between Mounting Facility Centers:
3.500 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
96 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Polarization Method:
Mating end
Connector Locking Method:
Friction
Operating Tempurature Rating:
Between -65.0 degrees celsius and 125.0 degrees celsius
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate glass filled single mating end
Contact Surface Treatment Specification:
Mil-g-45204 military specification single treatment response single mating end single contact grouping
Terminal Type

Qq-b-750 federal specification single material response single mating end single contact grouping

NSN 5935-01-320-6912

Electrical Receptacle Connector - Page 2 of 2



Insert Material Specification:

Mil-m-14f, type sdg-f military specification single material response single mating end

Included Contact Quantity:

96 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.096 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.