

View Online at <https://aerobasegroup.com/nsn/5935-01-320-7815>

**Body Style:**

Straight shape

**Overall Length:**

Between 7.095 inches and 7.105 inches

**Overall Height:**

0.983 inches

**Overall Width:**

Between 0.595 inches and 0.605 inches

**Environmental Protection:**

Humidity resistant

**Unthreaded Mounting Hole Diameter:**

Between 0.133 inches and 0.139 inches

**Distance Between Mounting Facility Centers:**

Between 6.795 inches and 6.805 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

2 rows of contacts non-inserted board single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

3.0 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

1000.0 single mating end single contact grouping

**Polarization Method:**

Guide pin/socket

**Shell Type:**

Solid

**Connector Locking Method:**

Friction

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

**Insert Material:**

Plastic polyamide glass filled single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204, type 2, grade c, cl 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 1 federal specification 2nd treatment response single mating end single contact grouping

**Terminal Type:**

Wire wrap single mating end single contact grouping

**Contact Material Specification:**

Qq-c-533 federal specification single material response single mating end single contact grouping

**Guide Design And Location:**

Key shape socket left-hand at 5 oclock

**Shell Material:**

Aluminum alloy 6061

**Shell Surface Treatment:**

Anodize

**Shell Surface Treatment Specification:**

Mil-a-8625, type 2, cl 1 military specification single treatment response

**Shell Material Specification:**

Qq-a-200/8 federal specification single material response

**Insert Material Specification:**

Mil-m-20693, type 1 military specification single material response single mating end

**Included Contact Quantity:**

116 single mating end single contact grouping

**Included Contact Type:**

Round socket single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.116 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.