NSN 5935-01-320-9372

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-320-9372

Body Style:
Straight type
Overall Length:
4.795 inches
Overall Height:
0.725 inches
Overall Width:
0.590 inches
Unthreaded Mounting Hole Diameter:
Between 0.112 inches and 0.117 inches
Distance Between Mounting Facility Centers:
Between 4.467 inches and 4.483 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
3.0 single mating end single contact grouping
Polarization Method:
Mating end
Connector Locking Method:
Friction
Operating Tempurature Rating:
Between -65.0 degrees celsius and 125.0 degrees celsius
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic polyester single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 1, grade c, cl 00 military specification single treatment response single mating end single contact grouping
Terminal Type:
Pin single mating end single contact grouping
Contact Material Specification:

Included Contact Quantity:

140 single mating end single contact grouping

Qq-c-530 federal specification single material response single mating end single contact grouping

NSN 5935-01-320-9372

Electrical Receptacle Connector - Page 2 of 2



Included Contact Type:
Brush socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.140 gold grains, troy
Precious Material:
Gold

Shelf Life:

Unit Of Measure:

__

N/a

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.