

View Online at <https://aerobasegroup.com/nsn/5935-01-320-9750>

Body Style:

Angle shape, pcb type

Overall Length:

Between 6.420 inches and 6.440 inches

Overall Height:

0.930 inches

Overall Width:

0.430 inches

Environmental Protection:

Humidity resistant and salt water resistant and thermal shock resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

Between 0.073 inches and 0.077 inches

Distance Between Mounting Facility Centers:

Between 6.245 inches and 6.255 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

Polarization Method:

Guide pin/socket

Connector Locking Method:

Friction

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate glass filled single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, class 1, grade c military specification 1st treatment response single mating end single contact grouping and qq-n-290, class 1 federal specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Printed circuit single mating end single contact grouping

Guide Design And Location:

D shape pin right-hand at 2 o'clock

Insert Material Specification:

Mil-m-14, type sdg-f military specification single material response single mating end

Included Contact Quantity:

116 single mating end single contact grouping

Included Contact Type:

Flat pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.116 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.