NSN 5935-01-321-4024

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-321-4024

Body Style:
Straight shape
Overall Length:
Between 0.915 inches and 0.935 inches
Overall Height:
0.539 inches
Overall Width:
0.308 inches
Environmental Protection:
Heat resistant and cold resistant
Unthreaded Mounting Hole Diameter:
Between 0.088 inches and 0.096 inches
Distance Between Mounting Facility Centers:
0.715 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
"2, 15" single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
3.0 single mating end single contact grouping
Polarization Method:
Mating end
Shell Type:
Solid
Connector Locking Method:
Friction
Operating Tempurature Rating:
Between -55.0 degrees celsius and 125.0 degrees celsius
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end or plastic single mating end
Contact Surface Treatment Specification:

Mil-g-45204, type 2, grade c, cl 1 military specification single treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

NSN 5935-01-321-4024

Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Aluminum
Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-416, cl 3, type 2 federal specification single treatment response
Shell Material Specification:
Mil-c-83513 military specification single material response
Insert Material Specification:
Mil-m-14, ty gdi-30-f, or ty sdg-f military specification 1st material response single mating end or mil-m-24519, ty glcp-30f military
specification 2nd material response single mating end
Included Contact Quantity:
15 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.015 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.