

View Online at <https://aerobasegroup.com/nsn/5935-01-321-7229>

Body Style:

Right angle, type

Overall Length:

Between 6.425 inches and 6.435 inches

Overall Height:

0.530 inches

Overall Width:

0.450 inches

Unthreaded Mounting Hole Diameter:

Between 0.073 inches and 0.077 inches

Distance Between Mounting Facility Centers:

Between 6.195 inches and 6.205 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

3 rows of contacts non-inserted board single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

Polarization Method:

Guide pin/socket

Shell Type:

Solid

Connector Locking Method:

Friction

Terminal Location:

Side single mating end single contact grouping

Contact Material:

Copper alloy 260 single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic polyamide single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, grade c, cl 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 1 federal specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Pin single mating end single contact grouping

Contact Material Specification:

Qq-b-613 federal specification single material response single mating end single contact grouping

Guide Design And Location:

Key shape pin left-hand at 5 oclock

Shell Material:

Aluminum alloy 6061

Shell Surface Treatment:

Anodize

Shell Surface Treatment Specification:

Mil-a-8625, type 2 military specification single treatment response

Shell Material Specification:

Qq-a-200/8 federal specification single material response

Insert Material Specification:

Mil-m-20693, type 1 military specification single material response single mating end

Included Contact Quantity:

174 single mating end single contact grouping

Included Contact Type:

Flat pin single mating end single contact grouping

Special Features:

Every tenth insulator bushing black in color

Color:

Natural

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.174 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.