NSN 5935-01-321-8946

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-321-8946

Thread Direction:
Right-hand
Body Style:
Straight shape
Overall Length:
1.516 inches
Overall Height:
0.670 inches
Overall Width:
0.267 inches
Distance Between Mounting Facility Centers:
1.200 inches
Threaded Device Type:
Mounting stud
Mating End Quantity:
1
Contact Position Arrangement Style:
17 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Polarization Method:
Guide pin/socket
Connector Locking Method:
Friction
Thread Size:
1.6 millimeters
Thread Pitch In Millimeters:
0.35
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping or gold single mating end single contact
grouping and copper single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end

Mil-g-45204, type 2, cl 1, grade c military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 2

federal specification 2nd treatment response single mating end single contact grouping or mil-g-45204, type 2, cl 1, grade c military specification 3rd treatment response single mating end single contact grouping and mil-c-14550, cl 4 military specification 4th treatment

Contact Surface Treatment Specification:

response single mating end single contact grouping

NSN 5935-01-321-8946

Electrical Receptacle Connector - Page 2 of 2



Guide Design And Location:

Key shape socket left-hand at 9 oclock and key shape socket right-hand at 9 oclock

Thread Tolerance Class:

6h external

Included Contact Quantity:

17 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.017 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Iso s

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.