

View Online at <https://aerobasegroup.com/nsn/5935-01-322-0869>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape w/flange w/cover

Unable To Decode:

Unable to decode and unable to decode

Overall Height:

4.500 inches

Mounting Hole Circle Radius:

2.812 inches

Overall Diameter:

6.125 inches

Environmental Protection:

Vibration resistant and shock resistant and corrosion resistant

Threaded Device Type:

Mounting stud

Mating End Quantity:

1

Contact Position Arrangement Style:

Mar-00 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

40.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

450.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Friction

Features Provided:

Grounded contact

Thready Qty Per Inch (tpi):

16

Thread Size:

0.380 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy 175 single mating end single contact grouping

Contact Surface Treatment:

Silver single mating end single contact grouping

Insert Material:

Plastic single mating end

Contact Surface Treatment Specification:

Qq-s-365 federal specification single treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Contact Material Specification:

Mil-c-46087 military specification single material response single mating end single contact grouping

Shell Material:

Copper alloy

Insert Material Specification:

Mil-m-14, type mai-60 military specification single material response single mating end

Included Contact Quantity:

3 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Special Features:

Furnished items - wire rope and protective cover

Precious Material And Location:

Contact surfaces silver

Precious Material And Weight:

0.003 silver grains, troy

Precious Material:

Silver

Test Data Document:

81349-mil-r-2726 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Uns

Specification Data:

81349-mil-r-2726/14 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

1-6921-6

Mil-std (military Standard):

Mil-c-46087 spec.