NSN 5935-01-322-6584

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-322-6584

Body Style:

Straight type

Overall Length:

2.200 inches

Overall Width:

Between 0.289 inches and 0.302 inches

Body Height:

Between 0.472 inches and 0.487 inches

Environmental Protection:

Shock resistant and vibration resistant and corrosion resistant and humidity resistant and fungus resistant

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end 1st contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end 1st contact grouping

Polarization Method:

Mating end

Connector Locking Method:

Friction

Terminal Location:

Back single mating end 1st contact grouping

Contact Material:

Copper alloy single mating end 1st contact grouping

Contact Surface Treatment:

Gold single mating end 1st contact grouping and nickel single mating end 1st contact grouping or gold single mating end 1st contact grouping and copper single mating end 1st contact grouping

Insert Material:

Plastic diallyl phthalate glass filled single mating end or plastic polyester glass filled single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, cl 1, grade c military specification 1st treatment response single mating end 1st contact grouping and qq-n-290, cl 2 federal specification 2nd treatment response single mating end 1st contact grouping or mil-g-45204, type 2, cl 1, grade c military specification 3rd treatment response single mating end 1st contact grouping and mil-c-14550, cl 4 military specification 4th treatment response single mating end 1st contact grouping

Terminal Type:

Tab, solder lug single mating end 1st contact grouping

Contact Material Specification:

Qq-c-530 federal specification single material response single mating end 1st contact grouping or qq-c-533 federal specification single material response single mating end 1st contact grouping or qq-b-750 federal specification single material response single mating end 1st contact grouping

Insert Material Specification:

Mil-m-14, ty sdg-f or ty gdi-30f military specification 1st material response single mating end or mil-m-24519, ty gpt-30f or gst-40f military specification 2nd material response single mating end

NSN 5935-01-322-6584

Electrical Receptacle Connector - Page 2 of 2



Special Features:
Right-hand end guide is silver; left-hand end guide is gold
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.033 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.