

View Online at <https://aerobasegroup.com/nsn/5935-01-322-7934>

**Body Style:**

Straight shape

**Overall Length:**

8.820 inches

**Overall Width:**

Between 0.490 inches and 0.510 inches

**Unthreaded Mounting Hole Diameter:**

Between 0.130 inches and 0.136 inches

**Distance Between Mounting Facility Centers:**

Between 8.490 inches and 8.510 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

4 rows of contacts non-inserted board single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

3.0 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

300.0 single mating end single contact grouping

**Polarization Method:**

Guide pin/socket

**Shell Type:**

Solid

**Connector Locking Method:**

Friction

**Operating Temperature Rating:**

Between -55.0 degrees celsius and 105.0 degrees celsius

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

**Insert Material:**

Plastic diallyl phthalate glass filled single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204, type 2, cl 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 1 federal specification 2nd treatment response single mating end single contact grouping

**Guide Design And Location:**

D shape pin left-hand top at 9 o'clock and d shape pin right-hand top at 9 o'clock

**Shell Material:**

Aluminum alloy 6061 or aluminum alloy 6063

**Shell Surface Treatment:**

Anodize

**Shell Surface Treatment Specification:**

Mil-a-8625, type 2, cl 2 military specification single treatment response

**Shell Material Specification:**

Qq-a-200/8 federal specification 1st material response or qq-a-200/9 federal specification 2nd material response

**Insert Material Specification:**

Mil-m-14, ty sdg-f military specification single material response single mating end

**Included Contact Quantity:**

304 single mating end single contact grouping

**Included Contact Type:**

Flat pin single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.304 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.