

View Online at <https://aerobasegroup.com/nsn/5935-01-323-2946>

Thread Class:

2a and 2a

Thread Direction:

Right-hand and right-hand

Body Style:

Straight shape

Overall Length:

Between 1.302 inches and 1.322 inches

Overall Diameter:

Between 0.615 inches and 0.635 inches

Environmental Protection:

Corrosion resistant and moisture resistant

Distance From Mounting Shoulder To Front Face:

Between 0.456 inches and 0.466 inches

Threaded Device Type:

Back shell and mounting bushing

Mating End Quantity:

2

Contact Position Arrangement Style:

Sma 2nd mating end

Contact Removability:

Nonremovable all mating ends single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

350.0 all mating ends single contact grouping

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 all mating ends single contact grouping

End Application:

6625-01-165-9406 plug-in unit, electronic test equipment amplifier

Thready Qty Per Inch (tpi):

36 and 28

Thread Size:

0.250 inches and 0.500 inches

Contact Material:

Copper alloy all mating ends single contact grouping

Contact Surface Treatment:

Gold all mating ends single contact grouping or silver all mating ends single contact grouping

Insert Material:

Plastic polytetrafluoroethylene all mating ends

Contact Surface Treatment Specification:

Mil-g-45204 military specification 1st treatment response all mating ends single contact grouping or qq-s-360 federal specification 2nd treatment response all mating ends single contact grouping

Contact Material Specification:

Qq-c-530 federal specification single material response all mating ends single contact grouping

Shell Material:

Copper alloy 360

Shell Surface Treatment:

Nickel alloy

Shell Material Specification:

Qq-b-626 federal specification single material response

Included Contact Quantity:

1 all mating ends single contact grouping

Bushing Accommodation Hole Shape:

Round w/double flat

Included Contact Type:

Coaxial socket all mating ends single contact grouping

Precious Material And Location:

Contact surfaces gold or contact surfaces silver

Precious Material And Weight:

0.005 gold grains, troy or 0.005 silver grains, troy

Precious Material:

Gold or silver

Thread Series Designator:

Uns and unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.