## NSN 5935-01-323-6763

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-323-6763

**Body Style:** 

Rectangular shape, angle

**Overall Length:** 

Between 1.198 inches and 1.228 inches

**Overall Height:** 

Between 0.578 inches and 0.663 inches

**Overall Width:** 

Between 0.722 inches and 0.732 inches

**Environmental Protection:** 

Corrosion resistant and humidity resistant and shock resistant and vibration resistant

**Unthreaded Mounting Hole Diameter:** 

Between 0.115 inches and 0.125 inches

**Distance Between Mounting Facility Centers:** 

Between 0.979 inches and 0.989 inches

**Mating End Quantity:** 

1

## **Contact Position Arrangement Style:**

9 single mating end

**Contact Removability:** 

Nonremovable single mating end single contact grouping

**Polarization Method:** 

Mating end

Shell Type:

Solid

**Connector Locking Method:** 

Friction

**Operating Tempurature Rating:** 

Between -55.0 degrees celsius and 125.0 degrees celsius

**Features Provided:** 

Pre-tinned terminal

**Terminal Location:** 

Side single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping and nickel single mating end single contact grouping

**Insert Material:** 

Plastic diallyl phthalate glass filled single mating end or plastic polyester glass filled single mating end

**Contact Surface Treatment Specification:** 

Mil-g-45204, type 2, grade c, cl 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 2 federal specification 2nd treatment response single mating end single contact grouping

**Terminal Type:** 

Printed circuit single mating end single contact grouping

## NSN 5935-01-323-6763

Electrical Receptacle Connector - Page 2 of 2



| Shell Material:   |
|---|
| Metal   |
| Shell Surface Treatment:  |
| Cadmium   |
| Insert Material Specification:  |
| Mil-m-14, ty sdg-f military specification 1st material response single mating end or mil-m-24519, ty gpt-30f or ty get-30f military specification |
| 2nd material response single mating end   |
| Included Contact Quantity:  |
| 9 single mating end single contact grouping   |
| Included Contact Type:  |
| Round socket single mating end single contact grouping  |
| Precious Material And Location:   |
| Contact surfaces gold   |
| Precious Material And Weight:   |
| 0.009 gold grains, troy   |
| Precious Material:  |
| Gold  |
| Test Data Document:   |
| 81349-mil-c-24308 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification      |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain               |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).                                 |
| Specification Data:   |
| 81349-mil-c-24308/23 government specification   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A039b0  |
| Mil-std (military Standard):  |
| Mil-g-45204 spec.   |
|   |
|   |