

View Online at <https://aerobasegroup.com/nsn/5935-01-323-9471>

Body Style:

Straight shape

Overall Length:

0.400 inches

Overall Height:

0.475 inches

Overall Width:

0.100 inches

Environmental Protection:

Heat resistant and cold resistant

Mating End Quantity:

1

Contact Position Arrangement Style:

1 row of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

1.0 single mating end single contact grouping

Connector Locking Method:

Friction

Operating Temperature Rating:

Between -65.0 degrees celsius and 105.0 degrees celsius

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and tin single mating end single contact grouping

Insert Material:

Plastic single mating end and glass single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification 1st treatment response single mating end single contact grouping

Criticality Code Justification:

Zzzy

Terminal Type:

Tab, solder lug single mating end single contact grouping

Included Contact Quantity:

4 single mating end single contact grouping

Included Contact Type:

Square socket single mating end single contact grouping

Special Features:

Item must comply with requirements of defense supply center columbus production standard no. Lo4326

Color:

Black

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.020 gold grains, troy

Precious Material:

Gold

Reference Number Differentiating Characteristics:

Reference number differentiating material will be in accordance with naval inventory control point activity hx quality control. Manufacturing and testing specifications available at the dla icp.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.