## NSN 5935-01-324-2324

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-324-2324

**Body Style:** 

Straight shape, internal coupling w/strain relief

**Body Length:** 

Between 3.670 inches and 3.710 inches

**Overall Diameter:** 

0.836 inches

**Environmental Protection:** 

Shock resistant and vibration resistant and thermal shock resistant and salt water resistant and humidity resistant

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

6 single mating end

**Contact Removability:** 

Nonremovable single mating end single contact grouping

**Polarization Method:** 

Keyway or multiple keyway

**Insert Position In Deg:** 

0.0

**Shell Type:** 

Solid

**Connector Locking Method:** 

Bayonet slot

**Connector Cable Strain Relief Method:** 

Cord protector

**Features Provided:** 

Pre-tinned terminal

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping and nickel single mating end single contact grouping

**Insert Material:** 

Plastic diallyl phthalate single mating end

**Contact Surface Treatment Specification:** 

Mil-g-45204 military specification 1st treatment response single mating end single contact grouping and qq-n-290 federal specification 2nd treatment response single mating end single contact grouping

**Terminal Type:** 

Solder well single mating end single contact grouping

**Contact Material Specification:** 

Qq-b-626, 1/2 hard federal specification single material response single mating end single contact grouping

**Shell Material:** 

Aluminum alloy 2011 and steel comp 303

## NSN 5935-01-324-2324

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.

Electrical Plug Connector - Page 2 of 2



## **Shell Surface Treatment:** Anodize and passivate **Shell Surface Treatment Specification:** Qq-p-35 federal specification 2nd treatment response **Shell Material Specification:** Qq-a-225/3, t3 federal specification 1st material response **Insert Material Specification:** Mil-m-14, type sdg-f or type gdf-30f or type mdg military specification single material response single mating end **Included Contact Quantity:** 6 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.030 gold grains, troy **Precious Material:** Gold Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig: