

View Online at <https://aerobasegroup.com/nsn/5935-01-324-2324>

Body Style:

Straight shape, internal coupling w/strain relief

Body Length:

Between 3.670 inches and 3.710 inches

Overall Diameter:

0.836 inches

Environmental Protection:

Shock resistant and vibration resistant and thermal shock resistant and salt water resistant and humidity resistant

Mating End Quantity:

1

Contact Position Arrangement Style:

6 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Bayonet slot

Connector Cable Strain Relief Method:

Cord protector

Features Provided:

Pre-tinned terminal

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification 1st treatment response single mating end single contact grouping and qq-n-290 federal specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Contact Material Specification:

Qq-b-626, 1/2 hard federal specification single material response single mating end single contact grouping

Shell Material:

Aluminum alloy 2011 and steel comp 303

Shell Surface Treatment:

Anodize and passivate

Shell Surface Treatment Specification:

Qq-p-35 federal specification 2nd treatment response

Shell Material Specification:

Qq-a-225/3, t3 federal specification 1st material response

Insert Material Specification:

Mil-m-14, type sgd-f or type gdf-30f or type mdg military specification single material response single mating end

Included Contact Quantity:

6 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.030 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.