Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-324-5845

Body Style:

Rectangular shape, angle

Overall Length:

Between 2.073 inches and 2.103 inches

Overall Height:

Between 0.479 inches and 0.509 inches

Overall Width:

0.740 inches

Environmental Protection:

Corrosion resistant and humidity resistant and shock resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

Between 0.115 inches and 0.125 inches

Distance Between Mounting Facility Centers:

Between 1.847 inches and 1.857 inches

Mating End Quantity:

Contact Position Arrangement Style:

25 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Polarization Method:

Mating end

Shell Type:

Solid

1

Connector Locking Method:

Friction

End Application:

5805-01-188-3993 central office, telephone, automatic

Operating Tempurature Rating:

Between -55.0 degrees celsius and 125.0 degrees celsius

Terminal Location:

Side single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate glass filled single mating end or plastic polyester glass filled single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, grade c, class 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290,

class 2 federal specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Pin single mating end single contact grouping

Electrical Receptacle Connector - Page 2 of 2



Shell Material:	
Metal	
Shell Surface Treat	ment:
Cadmium and chron	nate
Shell Surface Treat	tment Specification:
Qq-p-416, type 2, cla	ass 3 federal specification all treatment responses
Insert Material Spe	cification:
Mil-m-14, type sdg-f	military specification 1st material response single mating end or mil-m-24519, type gpt-30f or type get-30f military
specification 2nd ma	aterial response single mating end
Included Contact C	luantity:
25 single mating end	d single contact grouping
Included Contact T	уре:
Round socket single	e mating end single contact grouping
Precious Material A	And Location:
Contact surfaces go	ld
Precious Material A	And Weight:
0.025 gold grains, t	roy
Precious Material:	
Gold	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A039b0	
Mil-std (military Sta	andard):
Mil-g-45204 spec.	