

View Online at <https://aerobasegroup.com/nsn/5935-01-324-7435>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape, external coupling

**Overall Length:**

1.625 inches

**Overall Diameter:**

1.954 inches

**Environmental Protection:**

Thermal shock resistant and vibration resistant and shock resistant and humidity resistant

**Distance From Mounting Shoulder To Front Face:**

Between 0.879 inches and 0.899 inches

**Mounting Facility Thickness:**

Between 0.062 inches and 0.250 inches

**Threaded Device Type:**

Mounting bushing

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

22-78 single mating end

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

0.0

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet pin

**End Application:**

5805-01-188-3993 central office, telephone, automatic

**Operating Temperature Rating:**

Between -55.0 degrees celsius and 125.0 degrees celsius

**Thready Qty Per Inch (tpi):**

18

**Thread Size:**

1.500 inches

**Insert Material:**

Plastic single mating end

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium and chromate

**Shell Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification all treatment responses

**Shell Material Specification:**

Qq-a-591 federal specification single material response

**Bushing Accommodation Hole Shape:**

Round w/double flat

**Thread Series Designator:**

Unef

**Specification Data:**

28528-1135537 manufacturers source control

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0