NSN 5935-01-325-1614



Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-01-325-1614 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Angle shape, pcb, external coupling **Overall Length:** 0.600 inches **Overall Height:** 0.473 inches **Environmental Protection:** Shock proof and vibration proof and corrosion resistant and moisture resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** 0.060 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.200 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** Sma single mating end **Contact Removability:** Nonremovable single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Externally threaded shell **End Application:** 5865-01-070-2046 Thready Qty Per Inch (tpi): 36 **Thread Size:** 0.250 inches **Terminal Location:**

Side single mating end single contact grouping

Terminal Type:

Pin single mating end single contact grouping

Shell Material:

Steel

Included Contact Quantity:

1 single mating end single contact grouping

NSN 5935-01-325-1614

Electrical Receptacle Connector - Page 2 of 2



Bushina	Accommodation	Hole	Shape:
Jusiiiiiq	Accommodation	11016	Ullape.

Round

Included Contact Type:

Coaxial socket single mating end single contact grouping

Test Data Document:

81349-mil-c-39012 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Uns

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A039b0