Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-325-1614

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Angle shape, pcb, external coupling
Overall Length:
0.600 inches
Overall Height:
0.473 inches
Environmental Protection:
Shock proof and vibration proof and corrosion resistant and moisture resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
0.060 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.200 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
Sma single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell
End Application:
5865-01-070-2046
Thready Qty Per Inch (tpi):
36
Thread Size:
0.250 inches
Terminal Location:
Side single mating end single contact grouping
Terminal Type:
Pin single mating end single contact grouping
Shell Material:
Steel
Included Contact Quantity:
1 single moting and single contest grouping

1 single mating end single contact grouping

NSN 5935-01-325-1614

Electrical Receptacle Connector - Page 2 of 2



Bushing Accommodation Hole Shape:

Round

Included Contact Type:

Coaxial socket single mating end single contact grouping

Test Data Document:

81349-mil-c-39012 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Uns

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0