## NSN 5935-01-325-4429

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-325-4429

**Body Style:** 

Straight shape, flush mount

**Overall Length:** 

1.634 inches

**Overall Height:** 

Between 1.997 inches and 2.027 inches

**Overall Width:** 

Between 1.985 inches and 2.015 inches

**Environmental Protection:** 

Humidity resistant and salt water resistant and shock resistant and thermal shock resistant and vibration resistant

**Unthreaded Mounting Hole Diameter:** 

Between 0.118 inches and 0.122 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

1.720 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 1.725 inches and 1.765 inches

**Distance From Mounting Shoulder To Front Face:** 

Between 0.055 inches and 0.065 inches

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

57 single mating end

**Contact Removability:** 

Removable single mating end single contact grouping

**Polarization Method:** 

Mating end and guide pin/socket

Shell Type:

Solid

**Connector Locking Method:** 

Friction

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping

**Insert Material:** 

Plastic diallyl phthalate single mating end and plastic epoxy single mating end and plastic phenolic single mating end

**Contact Surface Treatment Specification:** 

Mil-g-45204 military specification single treatment response single mating end single contact grouping

**Terminal Type:** 

Crimp single mating end single contact grouping

# NSN 5935-01-325-4429

Electrical Receptacle Connector - Page 2 of 2



#### **Guide Design And Location:**

Hexagon shape female post left-hand at 12 oclock and hexagon shape female post center at 12 oclock and hexagon shape female post right-hand at 12 oclock

**Shell Material:** 

Aluminum alloy

**Shell Surface Treatment:** 

Cadmium and chromate

**Shell Surface Treatment Specification:** 

Qq-p-416 federal specification all treatment responses

**Shell Material Specification:** 

Qq-a-591 federal specification single material response or qq-a-367 federal specification single material response or qq-a-250 federal specification single material response

**Included Contact Quantity:** 

57 single mating end single contact grouping

**Included Contact Type:** 

Round pin single mating end single contact grouping

**Precious Material And Location:** 

Contact surfaces gold

**Precious Material And Weight:** 

0.057 gold grains, troy

**Precious Material:** 

Gold

### **Test Data Document:**

81349-mil-c-81659 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### **Specification Data:**

81349-mil-c-81659/31 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.