

View Online at <https://aerobasegroup.com/nsn/5935-01-326-1186>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling

Overall Length:

0.960 inches

Overall Height:

0.510 inches

Overall Width:

0.510 inches

Environmental Protection:

Corrosion resistant and vibration resistant and moisture resistant and thermal shock resistant

Unthreaded Mounting Hole Diameter:

Between 0.099 inches and 0.106 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 0.338 inches and 0.342 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 0.338 inches and 0.342 inches

Cable Entrance Diameter:

Between 0.195 inches and 0.216 inches

Distance From Mounting Shoulder To Front Face:

Between 0.310 inches and 0.340 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

Sma single mating end

Contact Removability:

Removable single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Connector Cable Strain Relief Method:

Crimp type

Thready Qty Per Inch (tpi):

36

Thread Size:

0.250 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic fluorinated ethylene propylene single mating end or plastic polytetrafluoroethylene single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, cl 1 military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Stainless steel

Shell Surface Treatment:

Passivate

Shell Surface Treatment Specification:

Mil-f-14072 military specification single treatment response

Insert Material Specification:

L-p-389 federal specification 1st material response single mating end or l-p-403 federal specification 2nd material response single mating end

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Coaxial socket single mating end single contact grouping

Precious Material And Location:

Contact surface gold

Precious Material And Weight:

0.005 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-39012 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Uns

Specification Data:

81349-mil-c-39012/58 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Mil-std (military Standard):

Mil-g-45204 spec.