NSN 5935-01-326-1409

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-326-1409 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, round **Overall Length:** 1.148 inches **Overall Diameter:** Between 1.300 inches and 1.310 inches **Environmental Protection:** Pressure proof **Threaded Device Type:** Mounting bushing **Mating End Quantity: Contact Position Arrangement Style:** 19-50 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Polarization Method:** Key, multiple key groove **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Friction Thread Length: 0.220 inches **Operating Tempurature Rating:** Between -65.0 degrees fahrenheit and 165.0 degrees fahrenheit Thready Qty Per Inch (tpi): 18 **Thread Size:** 1.062 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Nickel alloy single mating end single contact grouping

Insert Material:

Glass single mating end

NSN 5935-01-326-1409

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:
Pin single mating end single contact grouping
Shell Material:
Steel comp 1213 and steel
Shell Surface Treatment:
Copper and cadmium and tin
Shell Surface Treatment Specification:
Qq-p-416, cl 1, type 1 federal specification 2nd treatment response and mil-t-10727, type 1 military specification 3rd treatment response
Shell Material Specification:
Aisi-b1113 assn standard single material response or qq-s-627 federal specification single material response
Included Contact Quantity:
19 single mating end single contact grouping
Bushing Accommodation Hole Shape:
Round
Included Contact Type:
Round pin single mating end single contact grouping
Supplementary Features:
Mounting method - threaded body
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-t-10727 spec.