

View Online at <https://aerobasegroup.com/nsn/5935-01-326-2731>

**Body Style:**

Straight shape, round

**Overall Length:**

0.726 inches

**Overall Diameter:**

Between 1.172 inches and 1.202 inches

**Environmental Protection:**

Corrosion resistant and vibration resistant and shock resistant and moisture resistant and hermetic

**Mating End Quantity:**

1

**Contact Removability:**

Nonremovable single mating end all contact groupings

**Contact Maximum Ac Voltage Rating In Volts:**

600.0 single mating end all contact groupings

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

0.0

**Shell Type:**

Solid

**Connector Locking Method:**

Push-pull

**Operating Temperature Rating:**

Between -55.0 degrees celsius and 125.0 degrees celsius

**Terminal Location:**

Back single mating end all contact groupings

**Contact Material:**

Metal ferrous single mating end all contact groupings

**Contact Surface Treatment:**

Tin single mating end all contact groupings

**Insert Material:**

Glass single mating end

**Contact Surface Treatment Specification:**

Mil-t-10727 military specification single treatment response single mating end all contact groupings

**Terminal Type:**

Tab, solder lug single mating end all contact groupings

**Shell Material:**

Aluminum

**Shell Surface Treatment:**

Cadmium and tin

**Included Contact Quantity:**

3 single mating end 1st contact grouping

**Bushing Accommodation Hole Shape:**

Round

**Included Contact Type:**

Round pin single mating end all contact groupings

**Supplementary Features:**

Mounting method - solder

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-t-10727 spec.