NSN 5935-01-326-2736

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-326-2736 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Straight shape, internal coupling **Overall Length:** 0.528 inches **Overall Height:** 0.510 inches **Overall Width:** 0.510 inches **Environmental Protection:** Thermal shock resistant and corrosion resistant and moisture resistant **Unthreaded Mounting Hole Diameter:** Between 0.101 inches and 0.106 inches **Center To Center Distance Between Mounting Facilities Parallel To Height:** 0.340 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.340 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** Sma single mating end **Contact Removability:** Nonremovable single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Internally threaded coupling nut **End Application:** 5830-01-198-6445 repeater, radio **Operating Tempurature Rating:** Between -65.0 degrees celsius and 105.0 degrees celsius **Features Provided:** Captive contact Thready Qty Per Inch (tpi): 36

Thread Size:

0.250 inches

NSN 5935-01-326-2736

Electrical Receptacle Connector - Page 2 of 2



Terminal Location:	
Back single mating end single contact grouping	
Contact Material:	

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic polytetrafluoroethylene single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, cl 1, grade c military specification single treatment response single mating end single contact grouping

Terminal Type:

Pin jack single mating end single contact grouping

Contact Material Specification:

Qq-c-530, 1/2 hard federal specification single material response single mating end single contact grouping

Shell Material:

Steel comp 303

Shell Material Specification:

Astm-a-582 assn standard single material response

Insert Material Specification:

Mil-p-19468 military specification single material response single mating end

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Coaxial pin single mating end single contact grouping

Precious Material And Location:

Contact surface gold

Precious Material And Weight:

0.005 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Uns

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Nο

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.