

View Online at <https://aerobasegroup.com/nsn/5935-01-326-5003>

Body Style:

Right angle type

Overall Length:

Between 10.845 inches and 10.855 inches

Overall Height:

Between 0.819 inches and 0.829 inches

Overall Width:

Between 0.455 inches and 0.465 inches

Unthreaded Mounting Hole Diameter:

Between 0.095 inches and 0.100 inches

Distance Between Mounting Facility Centers:

Between 10.545 inches and 10.555 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

4 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

1.0 single mating end single contact grouping

Polarization Method:

Mating end

Connector Locking Method:

Friction

Operating Temperature Rating:

Between -55.0 degrees celsius and 105.0 degrees celsius

Terminal Location:

Side single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic polyphenylene single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification 1st treatment response single mating end single contact grouping

Terminal Type:

Pin single mating end single contact grouping

Included Contact Quantity:

392 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.392 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.