

View Online at <https://aerobasegroup.com/nsn/5935-01-326-5816>

Body Style:

Straight shape

Overall Length:

Between 2.620 inches and 2.650 inches

Overall Height:

0.665 inches

Overall Width:

Between 0.590 inches and 0.620 inches

Environmental Protection:

Corrosion resistant and humidity resistant and shock resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

Between 0.115 inches and 0.125 inches

Distance Between Mounting Facility Centers:

Between 2.401 inches and 2.411 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

78 single mating end

Contact Removability:

Removable single mating end single contact grouping

Polarization Method:

Mating end

Shell Type:

Solid

Connector Locking Method:

Friction

Operating Temperature Rating:

Between -55.0 degrees celsius and 125.0 degrees celsius

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate glass filled single mating end or plastic polyester glass filled single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, grade c, cl 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 2 federal specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Insert Material Specification:

Mil-m-14, ty sdg-f military specification 1st material response single mating end or mil-m-24519, ty gpt-30f or ty get-30f military specification 2nd material response single mating end

Included Contact Quantity:

78 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.078 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-24308 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-c-24308/4 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.