

View Online at <https://aerobasegroup.com/nsn/5935-01-326-7864>

Body Style:

Straight shape

Overall Length:

Between 0.795 inches and 0.805 inches

Overall Height:

0.290 inches

Overall Width:

Between 0.095 inches and 0.105 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

1 row of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end 2nd contact grouping

Contact Maximum Current Rating In Amps:

1.0 single mating end 2nd contact grouping

Connector Locking Method:

Friction

Terminal Location:

Back single mating end 2nd contact grouping

Contact Material:

Copper alloy single mating end 2nd contact grouping

Contact Surface Treatment:

Gold single mating end 2nd contact grouping and nickel single mating end 2nd contact grouping

Insert Material:

Plastic polyester glass filled single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification 1st treatment response single mating end 2nd contact grouping and qq-n-290 federal specification single treatment response single mating end 2nd contact grouping

Terminal Type:

Solder well single mating end 2nd contact grouping

Contact Material Specification:

Qq-c-553 federal specification single material response single mating end 1st contact grouping or astm b-194 assn standard single material response single mating end 1st contact grouping

Included Contact Quantity:

6 single mating end 2nd contact grouping

Included Contact Type:

Round socket single mating end 2nd contact grouping

Special Features:

Polarizing plug in contact position 1 also serves as shorting contact

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.007 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.